

# **DECLARATION OF PERFORMANCE**

### N.º DoP ACI-ICB-01-Rev4-20

1. Unique identification code of the product-type:

### ICB - Expanded Insulation Cork Board

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

### See the label product

 $\textbf{3.} \qquad \textbf{Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:} \\$ 

## For use as thermal insulation for buildings (see EN 13170) according to the manufacturer's specifications

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

Amorim Cork Insulation, S.A.
Rua de Meladas, 105
4535-186 Mozelos – Portugal
T: (+351) 227 419 100 | Email: info.aci@amorim.com | www.amorimcorkinsulation.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

#### no applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

Itecons - Instituto Investigação e Desenvolvimento Tecnológico para Construção, notified test laboratory nº 2211 (PT), report nº OMH067/15.

3. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

# no applicable

9. Declared performance: ICB - EN 13170 - L2 - W2 - T2 - CS(10)100 - TR50 - WS - MU20 - CC(0,8/0,4/10)5 - AFr35

Essential characteristics	Performance	Harmonised technical specification				
Reaction to fire, Euroclass characteristics	Reaction to fire	Euroclasse E	'			
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD				
Acoustic absorption index	Sound absorption	NPD				
Impact noise transmission index (for floors)	Dynamic stiffness	NPD				
	Thickness, aL	NPD				
	Compressibility	NPD				
	Air flow resistivity	AFr35				
Direct airborne sound insulation index	Air flow resistivity	AFr35				
Continuous Glowing combustion	Continuous Glowing combustion	NPD				
Thermal resistance	Thermal resistance	see Table A	EN 13170:2012+A1:201			
	Thermal conductivity	0,039 W/m.K				
	Thickness, aL	T1-T2( <i>d</i> L > 50 mm)				
Water permeability	Water absorption	ws				
Water vapour permeability	Water vapour transmission	MU20				
Compressive strength	Compressive stress at 10% deformation	CS(10)100				
	Point load	NPD				
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	satisfy				
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	satisfy				
	Durability characteristics	satisfy				
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR60 (25-60 mm) TR50 (65-300 mm)				
Durability of compressive strength against ageing/degradation	Compressive creep	CC(0,8/0,4/10)5				
NPD - No Performance Determined	•					

Amorim Cork Insulation, S.A.





10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

Mozelos, January 2020

Carlos Manuel Silva, CEO

**Table A:** Thermal resistance (R) in accordance with EN 13170:2012+A1:2015

Thickness, d₁ [mm]	20	25	30	35	40	45	50	55	60	65	70	75	80
Thermal resistance [m².K/W]	0,50	0,60	0,75	0,90	1,00	1,15	1,25	1,40	1,50	1,65	1,75	1,90	2,05
Thickness, d₁ [mm]	85	90	95	100	110	120	130	140	150	160	170	180	190
Thermal resistance [m².K/W]	2,15	2,30	2,40	2,55	2,80	3,05	3,30	3,55	3,85	4,10	4,35	4,60	4,85
Thickness, $d_L$ [mm]	200	210	220	230	240	250	260	270	280	290	300		
Thermal resistance [m².K/W]	5,10	5,35	5,60	5,90	6,15	6,40	6,65	6,90	7,15	7,40	7,65		